

Quick Fix™ Brush On - Supa Glue

Description

Quick Fix™ Brush On is great for all types of household repairs and comes with a convenient brush that makes repairs so easy. The bottle has special insert, so it won't spill if knocked over on a flat surface. The glue gives a strong bond in seconds and dries clear.

Product Information

Packaging	Size
Bottle	5mL

Uses

Quick Fix™ Brush On sticks to surfaces such as ceramic, china, paper, metal, wood and most plastics**

Features

- Easy Spread
- Brush On
- Anti-Spill Bottle*
- For Broad Spreading

Technical Details

Property	Typical Result
Technology	Cyanoacrylate
Colour	Dries Clear
Setting Time	60 seconds
Initial Bond Time	30 minutes
Max Bond Time	24 hours
Shear Strength - stainless steel (@25°C & 50%RH)	9.0 MPa
Shear Strength - Perspex (@25°C & 50%RH)	9.0MPa
Shear Strength - hoop pine (@25°C & 50%RH)	5.0MPa
Shear Strength - PVC (@25°C & 50%RH)	4.0MPa

Indicative data only, not intended for preparation of specifications

Surface Preparation

Ensure surfaces to be bonded are clean, dry, free of dust and close fitting.

Directions for Use

1. Unscrew cap and apply a small amount of glue to one surface only.
2. Bring surfaces together and apply slight pressure. Allow 30 minutes for sufficient bond strength for practical use. Maximum bond strength reached after 24 hours.
3. Ensure cap is replaced immediately after applying adhesive, as this prolongs the life of the brush applicator. Store in a cool, dry place out of direct sunlight.

Tips

- *Anti spill bottle if bottle tips into the horizontal position
- Do not invert bottle.

Clean Up

Uncured product may be removed with acetone. Cured product can be sanded and scraped

Storage

Store in a cool dry place out of direct sunlight.

Limitations

- **Not for polyethylene, polypropylene plastics. Use Selleys™ All Plastic Fix
- Not for glass. Use Selleys™ Araldite® Ultra Clear
- May cause some leather to discolour or harden – pre-test on an inconspicuous area

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com