

Description

Selleys Hold Up™ makes mounting, bonding or sticking tasks easier. With Hold Up™ you can forget screws, nails or clamps even when adhering on vertical surfaces.* Works on almost anything* even on indoor and outdoor surfaces. It is heat, UV and water resistant.

Product Information

Packaging	Size	Colour
Tube	130 g	White
Cartridge	290 mL	White/Off-white

Uses

Suitable for small jobs indoor or outdoors. Works on most materials: timber, concrete, MDF, particleboard, plasterboard, metals, some plastics,* glass, masonry, tiles and ceramics.

Technical Features

- Adjustable (for up to 15 minutes)
- Water resistant (not suitable for permanent water immersion)
- Paintable after 48 hours with waterbased paints
- Product holds objects on vertical surfaces*

Technical Details

Property	Typical Result
Appearance	Smooth white paste
Technology	Sil-X™
Cure Time	At least 48 hours
Skin Time	Approx. 45 min
Shelf Life	12 months

Indicative data only, not intended for preparation of specifications

How To Use (Cartridge)

1. Make sure the surfaces are clean, free from grease, grit and grime. Sand back any loose or peeling surfaces
2. Hold Up™ is a high performance product, for best results use a high quality caulking gun.

3. Face the V cut-out part of the nozzle upwards and apply the adhesive on one surface in long vertical beads approximately 5 cm apart (covering the full surface)
4. After applying the adhesive, press the surfaces together firmly, ensuring the adhesive spreads.

How To Use (Tube)

1. Make sure the surfaces are clean, free from grease, grit and grime. Sand back any loose or peeling surfaces
2. Pull off cape, unscrew nozzle and pierce membrane with the tip of the nozzle. Replace nozzle and cut along the second ridge
3. Cover one surface with Hold Up™ in long vertical strips
4. After applying the adhesive, press the surfaces together firmly, ensuring the adhesive spreads.

Clean Up

Immediately clean up with white spirits or turps before product cures.

Storage

Store in a cool dry place below 30°C.

Limitations

*Not for some plastics (PE, PP, PTFE) or some rubbers. Product holds up to 240 kg/m² (tube) or 360 kg/m² (cartridge) on vertical surfaces (eg walls). For heavy objects, overhead applications and non-porous materials such as glass and metals it is recommended that additional supports (eg clamps) are used during cure as a precaution. Must not be disturbed until cured (at least 48 hours)



Hold Up™

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com