

Selleys Auto Fix Windscreen Sealant

Description

Selleys Auto Fix Windscreen Sealant is designed to seal gaps around windows and windscreens to stop leaks quickly and effectively. It prevents the penetration of water, dust, and drafts through forming a waterproof seal unaffected by vibration and temperature extremes. The durable black silicone rubber seal is capable of withstanding joint movement of up to 25%

Product Information

Packaging	Size	Colour
Tube	100 ml	Black

Uses

For use on materials such as:

- Painted surfaces
- Rubber
- Glass
- Most plastics
- Metal

Features

- 100% Neutral cure silicone
- Forms a waterproof seal to stop leaks
- Seals out dirt and dust
- UV and weather resistant
- Set time 30 minutes

Technical Details

Property	Typical Result
Technology	100% Neutral Cure Silicone
Colour	Black
Density	1.02 g/ml
Application Temperature	-20°C to 50°C
Skin Time	5 minutes
Shore A Hardness (ASTM C661)	25
Elongation at Break	370%
Movement Capability (ASTM C719)	25%
Service Temperature (ASTM C1246:2017)	-40°C to 180°C
VOC (USEPA Test Methods 24)	26 g/L
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Clean the surface to leave no dirt and moisture.

Directions for Use

1. Remove any dirt or moisture between the rubber and windscreen glass. Clean with mineral turpentine and dry.
2. Remove cap, unscrew nozzle and remove seal. Replace nozzle and cut at a 45° angle.
3. If possible, insert nozzle between rubber and glass or rubber and metal. Squeeze tube with steady pressure ensuring product is pushed into joint and smooth off with a gloved finger.
4. If further smoothing is required, smooth before sealant skins.
5. Clean up, before sealant cures, with mineral turpentine. Cured sealant can only be removed by scraping or cutting.
6. After use, replace cap. Allow sealant to cure in nozzle and remove before next use.

Tips

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- Sealant skins in 5 minutes and dries to touch in 30 minutes and cures in 24 hours.

Clean Up

- Clean up, before sealant cures, with mineral turpentine. Cured sealant can only be removed by scraping or cutting.

Storage

- Store in a dry and cool place with temperature below 30 °C.
- Use within 24 months from date of production.

Limitations

- This sealant didn't adhere well to Natural rubber, NBR and Chloroprene/Neoprene

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com



Selleys Auto Fix Windscreen Sealant

Head Office 1 Gow Street, Padstow, NSW, 2211, Australia. Tel: 1300 555 205 (Aus); 0800 735 539 (NZ), Email: support.selleysau@selleys.com

All information contained in this Product Information Sheet is as accurate and up-to-date as possible at the time of printing. Products can be expected to perform as indicated in this sheet, so long as application procedures and maintenance are followed as recommended. Any other warranties that may be implied are expressly excluded, except the consumer guarantees under the Australian Consumer Law, where applicable, or any other non-excludable warranties under any State legislation, where applicable.