

## No More Gaps Bricks & Mortar

### Description

Selleys No More Gaps Bricks & Mortar is a textured, ready to use weather resistant gap filler available in a range of colour to match your existing mortar. It's mortar like texture allows easy repair of unsightly cracks and gaps in brickwork around the home.

### Product Information

Packaging	Size	Colour
Cartridge	440 g	Off White
Cartridge	440 g	Terracotta
Cartridge	440 g	Sandstone
Cartridge	440 g	Medium Grey
Cartridge	440 g	Charcoal

### Uses

Use Mortar Works™ for walls, pathways and tile roof ridge capping. It is suitable for materials such as brick, mortar/concrete, cement render, fibre cement sheeting.

### Features

- Mortar like texture
- More flexible than mortar
- Weather resistant
- UV resistant
- Mould resistant
- Water Clean up
- Sandable
- Paintable
- Low Shrink

### Technical Details

Property	Typical Result
Technology	Water-Based
Appearance	Lightly Textured Paste
Slump Resistance	No slump in gaps up to 20mm
Application Temperature	>5°C
Tooling Time	30 minutes*
Skin Time	30 minutes*
Tack-Free Time	60 minutes*

Indicative data only, not intended for preparation of specifications  
\*Depending on weather conditions

### Surface Preparation

Surface must be clean and free from loose material, grease and flaking/powdery paint.

### Directions for Use

1. Ensure surface is clean and free from loose material, grease and flaking/powdery paint.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle. Insert cartridge into caulking gun.
3. Apply with caulking gun, pushing product into gap or joint. Press into cracks and holes using a spatula or wet gloved finger.
4. Clean away excess from surfaces immediately using a damp cloth.
5. For larger cracks and holes, two applications may be necessary. Allow first application to dry before applying second. Hardens in 24 hours, depending on weather.
6. Protect from rain until firmly skinned.

### Tips

- For best results slightly dampen surface prior to application
- For use in fine cracks, eg. in cement render rub Selleys Mortar Works into cracks or use Selleys No More Cracks Exterior & Brick Render.
- If painting over apply undercoat before applying top coat for best results

### Clean Up

Uncured product may be removed with water. Cured product can be removed by sanding and scraping

### Storage

Do not apply or store below 5°C. Protect from rain until firmly skinned

### Limitations

- Not for areas of frequent water immersion.
- Not for replacing mortar in construction or for moving cracks.

### Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)