

Selleys No More Cracks Doors and Trim

Description

Selleys[®] No More Cracks™ Doors & Trim ready to use filler can be used inside or outside under gloss paints in applications such as doors, windows, architraves, trims and skirting boards. It gives a mirror like, durable finish with superior gloss retention.

For a perfect finish apply another thin coat filler, allow to dry before sanding, allow to dry before sanding lightly with fine sand paper.

Exterior applications should be protected from rain until painted over.

Product Information

Packaging	Size
Tub	270 g
Tub	580 g

Tips

Before painting, clean the surface with Selleys Sugar Soap. A clean surface aids paint adhesion.

For best results, apply an undercoat before your top coat of paint.

Uses

Selleys[®] No More Cracks™ Doors & Trim has excellent adhesion to timber, plaster, concrete, mortar and primed metal.

Clean Up

Clean tools and hands with water before filler dries.

Features

- Excellent gloss retention
- For interior and exterior use
- Easy to sand
- For use with Gloss Paints

Storage

Close lid tight after use and store in a cool dry place.

Technical Details

Property	Typical Result
Appearance	White Paste
Sand/Paint time	2-3 hours for 2-3 mm applications
Indicative data only, not intended for preparation of specifications	

Limitations

- Where movement occurs, use Selleys No More Gaps[®].
- Not suitable for exterior timber likely to absorb excessive amounts of water.

Surface Preparation

Ensure that the surface to be filled is clean and dry with no loose or powdery material.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com

Directions for Use

Exterior surfaces should be primed before filling.

Use a filling blade or scraper to firmly press the filler in and scrape of excess to minimise sanding.

Allow to dry for 2-3 hours depending on humidity, then sand with fine sand paper.