

Selleys Auto Fix Auto Sealant

Description

Selleys Auto Fix Auto Sealant is a versatile general purpose clear automotive sealant. The high strength adhesive forms a waterproof seal unaffected by vibration and temperature extremes. Selleys Auto Sealant is salt spray & detergent resistant and adheres to most auto and caravan materials.

Product Information

Packaging	Size	Colour
Tube	100 ml	Translucent

Uses

For use on materials such as:

- Glass
- Paint surfaces
- Fiberglass
- Most plastics
- Trim
- Most rubbers

Features

- 100% Neutral cure silicone
- Versatile general purpose
- Seals out water
- UV and weather resistant
- Set time 30 minutes

Technical Details

Property	Typical Result
Technology	100% Neutral Cure Silicone
Colour	Translucent
Density	1.02 g/ml
Application Temperature	-20°C to 50°C
Skin Time	5 minutes
Shore A Hardness (ASTM C661)	25
Elongation at Break	370%
Movement Capability (ASTM C719)	25%
Service Temperature (ASTM C1246:2017)	-40°C to 180°C
VOC (USEPA Test Method 24)	26 g/L
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Clean the surface to leave no dirt and moisture.

Directions for Use

1. Remove any dirt or moisture between application area. Clean with mineral turpentine and dry.
2. Remove cap, unscrew nozzle and remove seal. Replace nozzle and cut at a 45° angle.
3. To extrude, squeeze tube with steady pressure into application area and smooth off with a gloved finger.
4. If further smoothing is required, smooth before sealant skins.
5. Clean up, before sealant cures, with mineral turpentine. Cured sealant can only be removed by scraping or cutting.
6. After use, replace cap. Allow sealant to cure in nozzle and remove before next use.

Tips

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- Sealant skins in 5 minutes and dries to touch in 30 minutes and cures in 24 hours.

Clean Up

- Clean up, before sealant cures, with mineral turpentine. Cured sealant can only be removed by scraping or cutting.

Storage

- Store in a dry and cool place with temperature below 30 °C.
- Use within 24 months from date of production.

Limitations

- This sealant didn't adhere well to Natural rubber, NBR and Chloroprene/Neoprene

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com